


Second Target Station Project: IS - Target Assembly - Core Vessel



Aaron Jacques
Chris Anton
Lukas Bearden

4/2/2024 9:29 AM



This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Second Target Station Project

IS - TARGET ASSEMBLY - CORE VESSEL

Aaron Jacques
Chris Anton
Lukas Bearden

4/2/2024 9:29 AM

Prepared by
OAK RIDGE NATIONAL LABORATORY
Oak Ridge, TN 37831
managed by
UT-BATTELLE LLC
for the
US DEPARTMENT OF ENERGY
under contract DE-AC05-00OR22725

Approvals

Document Title		ISSUE DATE:
PREPARED BY Aaron Jacques	PROJECT Second Target Station	DOCUMENT NUMBER: S01020500-IST10209

	Signature / Date					
	Rev. 00	Date	Rev. 01	Date	Rev. 02	Date
Target Assembly Lead Engineer						
Core Vessel Lead Engineer						
Target Assembly Design Engineer						
Target TCCM						

Revision	Description
00	Initial Release

CONTENTS

CONTENTS.....	iii
IS - Target Assembly - Core Vessel.....	4
1. Boundary Loads.....	4
2. Target Access.....	4
2.1 Gama gate	6
3. Target Assembly Mounting Interface	6
4. Mounting and Support	6
5. Seal interface between core vessel and Target Assembly:	6
6. Core Vessel Feed Throughs	6
7. Core Vessel Environment relative to Target Assembly.....	7
7.1 Vacuum Operation	7
7.2 Helium Operation.....	7
8. Radiation Safety.....	7

IS - TARGET ASSEMBLY - CORE VESSEL

1. BOUNDARY LOADS

The target will impose the following maximum (bounding) loads to the core vessel. Note: Directions are per the STS global Coordinate system. Forces and moments are applied at the centroid of the lid interface as defined in Drawing TBD.

Table 1. Target Assembly Loads (TBR)

Load		kN			kN-m			Configuration	Comment
		F _x	F _y	F _z	M _x	M _y	M _z		
<i>Gravity</i>	D	0	-132	0	0	0	0	Operation	
<i>Imbalance</i>	L _ω	0.25	0	0.25	0.5	0	0.5	Operation	4.5Hz (amplitude shown)
<i>Vacuum Pressure</i>	P _{vac}	Per surface area of penetration						Operation	Vacuum
<i>Partial Pressure</i>	P _{He}	Per Surface area of penetration							Helium
<i>Start/Stop</i>	L _{start}	0	0	0	0	0.5	0	Operation	
<i>Segment Replacement</i>	L _{maint}				1.2		1.2	Maintenance	Moment is applied exclusively in either direction but not concurrently (rotated shaft with half the segments missing)
<i>Seismic</i>	E	±60	±21.6	±60	265	0	265	Operation	Horizontal components applied in worst case combination; not concurrently

For nominal gaps between Target Assembly and Core Vessel shielding, as well as tolerances, refer to drawing S03000000-M8U-8800-A10001.

The lower interface between the Core Vessel and the Target Assembly consists of the limit ring. The purpose of the ring is to prevent the shaft from swinging into the MRA during a seismic event. The ring is part of the Target Assembly scope and mounts to the Core Vessel lower shield block. Refer to drawing S03020000-M8U-8800-A10000 for dimensions. The lower shield block should mount the limit ring such that it can withstand a 40 kN seismic load.

2. TARGET ACCESS

The shielding near the target segment access area shall provide an easily removable shield component in accordance with S03020000-M8U-8800-A10000. The removable shielding plug shall be removable within a duration of 8 hours. *Note: This includes disconnecting water, attaching to remote handling fixtures, and lifting into cask* (Figure 1).

- The Core Vessel shall maintain access around the top of the removable shielding plug for personnel and tooling for segment removal.




Figure 1: Removable Shield Plug Removal In-Process

Geometry shall be present to guide a target segment out of the core vessel and back in. *NOTE: The desire is to guide a target segment heel pin into the alignment hole at the bottom of the shaft each time, and ensure that as long as the top vertical alignment is correct, that the lower portion is in the correct position (Figure 2).*




Figure 2: Target Segment Alignment Pin in Alignment Hole

2.1 GAMA GATE

The gama gate is within the Core Vessel WBS scope.

The gama gate consists of two steel-encase plates that reside over the area of the removable shielding plug. The purpose is to permit the removal of the removable shielding plug while still blocking the streaming gap while individuals are working near the top of the segment. The two plates allow the gate to slide to both sides of the opening to allow the removal and insertion of a target segment, as well as the removable shield plug.

- *NOTE: With the shield in place, the dose rate is within the allowable range of [TBD].*

3. TARGET ASSEMBLY MOUNTING INTERFACE

The core vessel shall provide a mounting interface with the geometry specified in *S03020000-M8U-8800-A10000* whose deflection and tolerances meet those laid out in *S03000000-M8U-8800-A10001*, for all load combinations specified in Table 1.

4. MOUNTING AND SUPPORT

The shielding below the target shaft shall be capable of supporting the shaft (16,000kg), during maintenance operations, without damage or permanent deformation. Additionally, the gap between the bottom of the shaft and the lower shield blocks should be such that target segments do not contact the MRA when the shaft is set on the lower shield block.

5. SEAL INTERFACE BETWEEN CORE VESSEL AND TARGET ASSEMBLY:

The interface between the Core Vessel and Target Assembly shall be a vacuum sealed interface that will allow 5mm of vertical compliance and 5mm of radial compliance. The seal shall be around the “SEAL ELEVATION” as shown in *S03020000-G8U-8800-A10000*.

Note: Preferably, the seal around the drive is split to permit segment removal without disconnecting the Process Water.

6. CORE VESSEL FEED THROUGHS

Two instances of feedthroughs in the Core Vessel lid structure are needed for the Target Assembly bearing assembly: bearing lubrication and seal purge gas.

- **Bearing Lubrication:** 2x Swagelok ¼” (TBR) fittings
- **Seal Purge Gas:** 1x Swagelok ¼” (TBR) fitting

As shown in Figure 3 below, the Core Vessel scope is to provide a female threaded pass-through for fittings provided by the Target Assembly scope.




Figure 3: Target Assembly and Core Vessel Feed-Through Scope Division

7. CORE VESSEL ENVIRONMENT RELATIVE TO TARGET ASSEMBLY

7.1 VACUUM OPERATION

Temperature:	20-40°C
Pressure:	$\leq 1 \times 10^{-1}$ Torr
Relative Humidity:	TBD
Target Assembly Leak Rate:	$< 1 \times 10^{-1}$ Torr-L/s

7.2 HELIUM OPERATION

Temperature:	20-40°C
Pressure:	$< 95,000$ Pa
Gas Purity	TBR 99.0%
Relative Humidity:	TBD
Target Assembly Leak Rate:	$< 1 \times 10^{-1}$ Torr-L/s

8. RADIATION SAFETY

Note: Radiation safety in the Target Assembly and Core Vessel are not captured in detail in this document. Target assembly and Core Vessel manage this interface by ensuring consistency between the MCNP & CAD model with respect to materials, locations, etc.