


Second Target Station Project: Target Station Shielding – Acquisition Strategy



Chris Anton
Hogan Knott
Cam Eiland
Darren Dugan
Mike Strong

April 2025



ORNL IS MANAGED BY UT-BATTELLE LLC FOR THE US DEPARTMENT OF ENERGY

The only OFFICIAL COPY of this document is the on-line electronic version in EDRM.

Before using a printed copy, verify that it is the most current version.

Draft. Not approved for public release.

DOCUMENT AVAILABILITY

Reports produced after January 1, 1996, are generally available free via OSTI.GOV.

Website www.osti.gov

Reports produced before January 1, 1996, may be purchased by members of the public from the following source:

National Technical Information Service
5285 Port Royal Road
Springfield, VA 22161
Telephone 703-605-6000 (1-800-553-6847)
TDD 703-487-4639
Fax 703-605-6900
E-mail info@ntis.gov
Website <http://classic.ntis.gov/>

Reports are available to US Department of Energy (DOE) employees, DOE contractors, Energy Technology Data Exchange representatives, and International Nuclear Information System representatives from the following source:

Office of Scientific and Technical Information
PO Box 62
Oak Ridge, TN 37831
Telephone 865-576-8401
Fax 865-576-5728
E-mail reports@osti.gov
Website <https://www.osti.gov/>

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Second Target Station Project

TARGET STATION SHIELDING – ACQUISITION STRATEGY

Chris Anton
Hogan Knott
Cam Eiland
Darren Dugan
Mike Strong

April 2025

Prepared by
OAK RIDGE NATIONAL LABORATORY
Oak Ridge, TN 37831
managed by
UT-BATTELLE LLC
for the
US DEPARTMENT OF ENERGY
under contract DE-AC05-00OR22725

Approvals

Document Title: Target Station Shielding Acquisition Strategy		ISSUE DATE: April 2025
PREPARED BY Chris Anton	PROJECT Second Target Station	DOCUMENT NUMBER: S03070000-MFP10000

	Signature / Date					
	Rev. 00	Date	Rev. 01	Date	Rev. 02	Date
Vessel Systems Lead Engineer Interface Systems Team Leader Target Systems Level 2 Manager						
Revision	Description					
00	Initial Release					

CONTENTS

CONTENTS.....	v
LIST OF FIGURES	vi
LIST OF ABBREVIATIONS.....	vii
1. Scope.....	1
2. References.....	1
3. Acquisition Strategy	1
3.1 Bulk Shielding Acquisition Strategy.....	1
3.2 Removable Shielding Acquisition Strategy	2
3.3 Core Vessel Baseplate.....	3
3.4 Bulk Shielding Liner Acquisition Strategy	3
3.5 Pipe Pan Acquisition Strategy.....	4

LIST OF FIGURES

Figure 1: CAD image of TSS Bulk Shielding.....	2
Figure 2: CAD image showing the AIC removable shielding (left) and Pipe Pan removable shield plates (right).....	3
Figure 3: CAD images of the top and bottom of the Core Vessel Baseplate.....	3
Figure 4: CAD images of the top and bottom of the Bulk Shielding Liner	4
Figure 5: CAD image showing the Pipe Pan	5

LIST OF ABBREVIATIONS

COTS	Commercial Off The Shelf
CV	Core Vessel
TS	Target Systems
TSS	Target Station Shielding
STS	Second Target Station

1. SCOPE

This document describes the acquisition strategy for the Target Station Shielding (TSS) scope within the Target Systems (TS) group of the Second Target Station (STS) project.

2. REFERENCES

Ref	Document Title	Document Number
[1]	Target Station Shielding Fabrication and Manufacturing Strategy	S03070000-MFP10001
[2]	Target Station Shielding Cost Estimation	S03070000-MFP10002

3. ACQUISITION STRATEGY

The Target Station Shielding scope will be acquired in a series of build to print manufacturing subcontracts with an estimated value of \$2.4M, as seen in the Target Station Shielding Cost Estimation [2]. Target Station Shielding includes the following subsystems; Bulk Shielding, Removable Shielding, Core Vessel Baseplate, Bulk Shielding Liner and Pipe Pans. Due to the wide variety of component sizes and complexities, it is anticipated that several different vendors will be contracted to build various components of the TSS scope. A subset of TSS components are installed very early in the monolith installation process, however these components are expected to take much less time to fabricate than the Core Vessel (CV) that is installed in parallel with them. It is likely that the bulk shielding manufacturing contract will be split into two parts with the shielding below and around the Core Vessel nozzle extensions being ordered sooner than the remaining shielding to better sync with expected monolith installation activities.

3.1 BULK SHIELDING ACQUISITION STRATEGY

The bulk shielding will be constructed from low-cost carbon steel. Cobble or secondary plate steel similar to what was used on the FTS bulk shielding will be utilized. This type of steel offers a very low cost per pound price while still providing excellent radiation shielding performance. All bulk shielding blocks will be fabricated completely by an outside vendor. The method of construction of each shield block will be determined in collaboration with the shielding vendor. Stacked and welded plates is the most likely construction method to be employed. Each shield block will require final machining to produce drilled thru holes, blind tapped holes and outside profile features. Efforts will be made to minimize the tolerance requirements of these shield blocks to keep costs down as much as possible. Each shield block will be coated with an anti-corrosive coating to minimize rusting over the life of the facility. The Target Station Shielding manufacturing and fabrication strategy details all steps necessary to fabricate the bulk shielding [1]. Figure 1 below shows the collection of components that will be procured as part of the Bulk Shielding acquisition package.




Figure 1: CAD image of TSS Bulk Shielding

3.2 REMOVABLE SHIELDING ACQUISITION STRATEGY

The AIC removable shield blocks will be constructed from the same low-cost steel to fabricate the bulk shielding components. The form factor of these blocks (See Figure 2) may necessitate a different fabrication strategy from the bulk shielding blocks. Details of the manufacturing approach will be determined in collaboration with the selected shielding vendor during the procurement process. The pipe pan cover plates will also be fabricated from low-cost carbon steel, likely secondary plate steel. These plates are 50mm thick and contain basic features that are not technically challenging to machine. Alternative machining approaches such as water jet cutting or plasma cutting will be considered to reduce overall costs. The Target Station Shielding manufacturing and fabrication strategy details all steps necessary to fabricate the removable shielding [1].




Figure 2: CAD image showing the AIC removable shielding (left) and Pipe Pan removable shield plates (right)

3.3 CORE VESSEL BASEPLATE

The CV Baseplate will be constructed from 75mm thick carbon steel. Low cost secondary plate or conventional A36 plate may be used depending on the form factors available. The machined features are all straight forward and should not pose a machining challenge (See Figure 3), however the large form factor of the CV Baseplate may limit the potential vendor pool that can efficiently machine this part. The CV Baseplate is one of the first components installed in the monolith, and procurement should be timed to coordinate completion of the CV baseplate with completion of the CV. The Target Station Shielding manufacturing and fabrication strategy details all steps necessary to fabricate the CV Baseplate [1].




Figure 3: CAD images of the top and bottom of the Core Vessel Baseplate

3.4 BULK SHIELDING LINER ACQUISITION STRATEGY

The bulk shielding liner will be constructed from carbon steel with a combination of 75mm and 25mm finished thicknesses. Low-cost secondary plate steel will be employed where possible to save costs. The bottom section of the liner is constructed from 75mm thick plate and will likely be fabricated in sections and assembled/field welded together on site due to its large size. The Bulk Shielding Liner must be water

tight after all welding is complete. The side walls of the bulk shielding liner are 25 mm thick and will be rolled to the proper diameter and welded to the bottom section after installation in the monolith. Grout and anchor holes will be machined into the bottom plate prior to installation. Blind tapped anchor holes for mounting the first layer of bulk shielding will be located via survey and alignment and drilled/tapped in place using magnetic base drills to ensure accurate anchor hole locations. Figure 4 shows the general layout of the Bulk Shielding Liner. The Target Station Shielding manufacturing and fabrication strategy details all steps necessary to fabricate the Bulk Shielding Liner [1].




Figure 4: CAD images of the top and bottom of the Bulk Shielding Liner

3.5 PIPE PAN ACQUISITION STRATEGY

The pipe pans will be constructed from stainless steel sheet. They will be constructed in pieces and fit/field welded together in place after the bulk shielding is installed to form the finished pipe pan profile shown in Figure 5 below. Laser cutting will likely be employed to fabricate each pipe pan section due to its low cost when compared to traditional machining and better cleanliness for welding than water jet cutting. The Target Station Shielding manufacturing and fabrication strategy details all steps necessary to fabricate the pipe pans [1].




Figure 5: CAD image showing the Pipe Pan